



Features

2 rows with 25 contacts
Wire Gauge: AWG24/26 or AWG28/30

Electrical

Current rating: 1A
Contact resistance: 20m
Insulation resistance: 1000 M
Dielectric withstand voltage: 1000V.r.m.s.

Mechanical

Insertion force: 1.2N/pin
Extraction force: 0.2N/pin
Retention force: 10N/pin
Operating temperature: -40 ~ +105

特点

双排25列线缆连接器
适用线规: AWG24/26或AWG28/30
90度出线

电气特性

额定电流: 1 A
接触电阻: 20 m
绝缘电阻: 1000 M
耐电压: 1000 V.r.m.s.

机械特性

插入力: 1.2 N/pin
拔出力: 0.2 N/pin
保持力: 10 N/pin
适用环境: -40 ~ +105

1860-501-XX-1

电镀等级 (Grade of the plating)

代码(code)	触点镀层(Contacts plating)
2	GLASS I
3	GLASS II
4	GLASS III

线规号 (Wire gauge)

代码(code)	线规号(Wire gauge)
1	AWG24/26
2	AWG28/30

类型 (Type)

代码 (Code)	定义 (Definition)
1	公(Male)

引脚数量(Number of contacts)
50pin (50 contactors)

1860系列 (1860 Series)
90度出线 (Right Angle Output direction)

