


SCHEMATIC



P.C.B. LAYOUT

RoHS Compliance

5	CONTACT	P B S	1	Ag PLATED					
3	TERMINAL	BRASS	4	Ag PLATED	4	COVER BOARD	S U S	1	
1	FRAME	NYLON	1		2	KNOB	NYLON	1	
NO.	PART	MATERIAL	QTY	REMARKS	NO.	PART	MATERIAL	QTY	REMARKS
									TG 2-5

ISSUED SPECIFICATION

TITLE: MINIATURE SLIDE SWITCH (1P3T)



RATING:	DC 12V 0.1A
CONTACT RESISTANCE:	70mΩ max.
INSULATION RESISTANCE:	100MΩ AT 500V DC
WITHSTAND VOLTAGE:	AC 100V for 1 minute
OPERATION FORCE:	REFER ATTACH SPECIFICATION
SWITCHING LIFE:	10K cycles min.

MODEL NO:	MSS-13D19		
TOLERANCE	UNIT: MM	DWN.	<i>hro</i>
UP TO 1.0:±0.1	SCALE: 5:1	CHK'D.	<i>hro</i>
1.0 TO 10.0:±0.2	VERSION: 01	APPD.	<i>hro</i>
OVER 10.0:±0.3	DRWG NO:		