





RoHS
Compliance



SCHEMATIC



PCB LAYOUT



7	BALL	STEEL	2						
5	CONTACT	P B S	1	Ag PLATED	6	SPRING	STEEL WIRE	1	
3	TERMINAL	BRASS	4	Ag PLATED	4	TERMINAL BASE	PHENOL RESIN	1 NATURAL	
1	FRAME	SPCC	1	Ni PLATED	2	KNOB	POM+SPCC	1 M 14	
NO	PART	MATERIAL	QTY	REMARKS	NO	PART	MATERIAL	QTY	REMARKS

ISSUED

SPECIFICATION

TITLE: SLIDE SWITCH (1P2T)



RATING: DC 30V 0.3A
 CONTACT RESISTANCE: 30mΩ max.
 INSULATION RESISTANCE: 500MΩ at 500V DC
 WITHSTAND VOLTAGE: AC 500V for 1 minute
 OPERATION FORCE: REFER ATTACH SPECIFICATION
 SWITCHING LIFE: 10K cycles min.

MODEL NO: SS-12H19(M14)

TOLERANCE
 UP TO 1.0:±0.1
 1.0 TO 10.0:±0.2
 OVER 10.0:±0.3

UNIT: MM
 SCALE: 2:1
 VERSION: 01
 DRWG NO:

DWN.
 CHK'D.
 APPD.