



REV.	NOTES	DATE
A	RELEASED	2006/08/29
B	增加料號ASC+0100-40B8	2007/01/03

- NOTES:
- MATERIALS:
 - Insulator:P.C
 - Contact:Brass 0.5t.Gold Plated
 - SPECIFICATIONS
 - Current Rating:1.5 A.
 - Dielectric Strength:500V AC for one minute.
 - Insulator Resistance:1000M ohms Min,at 500V DC
 - Contact Resistance:20m ohms Max
 - Operation Temperature:-20°C ~ 85°C

PART NO	MATERIAL	PLATED
ASC+0100-40C12	PC	GOLD PLATED
ASC+0100-40B8	PBT	TIN PLATED

單位 (UNITS)	mm
數量 (QTY)	N/A
材料 (MTR'L)	SEE NOTE
處理 (FINISH)	SEE NOTE

DIMENSIONS TOLERANCE		圖名 (NAME)	
METRIC	0 = ±.15 .00 = ±.10 .000 = ±.XXX .0000 = ± ANG. = ±5°	中心柱滿PIN新改 PC無毒	
繪圖 (DRAW)		料號 (PART NUMBER)	ASC+0100-40C12
設計 (DE'N)		圖號 (DRAW NUMBER)	RASC010040C12
審核 (CHK'K)		圖檔 (FILE NAME .DWG)	E:GCT/P/SC/3/000
核准 (APP'D)		比例 (SCALE)	1/1
		圖紙 (S/ZE)	A4
		頁次 (SHEET)	1
		版本 (REV.)	B