



NOTES:

1. MATERIALS

- 1.1 Insulator: P.C. Or PBT
- 1.2 Contact: Brass 0.3t. Tin Plated Or Gold Plated

2. SPECIFICATIONS

- 2.1 Current Rating: 3.0Amp
- 2.2 Dielectric Strength: 1000V AC for one minute
- 2.3 Insulator Resistance: 1000M ohms Min
- 2.4 Contact Resistance: 30m ohms Max
- 2.5 Operation Temperature: -55°C to +105°C

DIMENSIONS TOLERANCE

METRIC
 0 = ±.3
 .00 = ±.20
 .000 = ±.XXX
 .0000 = ±
 ANG. = ±.5°

| | | | | | | | |
|-------------|----------|------------------|-------------------|------------------|--------------|---------------------|---------------|
| 單位 (UNITS) | mm | 圖名 (NAME) | 中心挂滿PIN鍍錫 (YB) PC | | | | |
| 數量 (QTY) | N/A | 料號 (PART NUMBER) | ASC+0100-40C1 | 圖號 (DRAW NUMBER) | RASC010040C1 | 圖檔 (FILE NAME .DWG) | E:GCT/A/SC/01 |
| 材料 (MTR'L) | SEE NOTE | 繪圖 (DRAW) | | 比例 (SCALE) | 1/1 | 圖紙 (SHEET) | A4 |
| 處理 (FINISH) | SEE NOTE | 設計 (DE'N) | | 頁次 (SHEET) | 1 | 版本 (REV.) | A |
| 審核 (APP' D) | | 審校 (CHK' K) | | | | | |

| REV. | NOTES | DATE |
|------|----------|------------|
| A | RELEASED | 2003/10/10 |