



P.C.B LAYOUT

REV	DESCRIPTION	MODIFICATION	DATE
A/0	新制定		05.08.16
A/1	變更一	料號編碼變更	06.05.12

RoHS

***MATERIAL**
 BODY : PBT30% UL 94V-0 RATED, COLOR: WHITE
 LATCH : PA66+30% G.F 94V-0 RATED, COLOR: WHITE
 CONTACTS : BRASS
 CONTACT PLATING : GOLD PLATING OVER NICKEL ON CONTACT AREA TIN PLATING ON TERMINAL

***MECHANICAL**
 MATING FORCE : 4.5 KG MAX. @ 25 MM/MINUTE
 UNMATING FORCE: 1.0 KG MIN. AND 4.0 KG MAX. @25 MM/MINUTE
 DURABILITY: 100 MATING CYCLES

***ELECTRICAL SPECIFICATION**
 INSULATION RESISTANCE : 1000 MEGOHMS MIN
 DIELECTRIC WITHSTANDING VOLTAGE : 500 V DC RMS ± 50 V.60 HZ
 CURRENT RATING: 1.5 AMPERES MIN
 SHELL RESISTANCE: 50 MIILOHMS MAX. INITIAL; 50 MIILOHMS
 MAX.CHANGE FROM INITIAL
 CONTACT RESISTANCE : 20 MIILOHMS MAX.

***ENVIRONMENTAL**
 OPERATING TEMPERATURE : -20° TO 85°

***HOW TO ORDER**

PART NUMBER :

DF 245 R 8-3 2 2 01 B2



未標示公差尺寸值		TITLE: DVI(24+0)8F90度附4.75*11.8		DRAWN BY 聶玉忠	
METRIC	.0=±0.35	PRODUCT NO: DF240R8-32201B2	DESIGNED BY	APPROVAL BY	
	.00=±0.25	FILE NO: ZK-3-D-001	SCALE	UNIT	mm
	.000=±0.15		1:1	REV	A/1
					COSI-411